

DS1505

Industrial Vacuum






Compact vacuum equipped with a side channel pump installed directly on the top of the machine. It is suitable to collect many types of solid and dusty materials, and is also able to collect liquids. It can work continuously with the addition of a liquid level sensor, and is available in several different versions.

Technical Data

		DS1505M	DS1505
Power	kW	2,2 (2,2 230V)	3
Rated Current	A	4 (15)	7
Voltage	V - Hz	200/240 - 50	400 - 50
Eff. flow (max)	m ³ /h	300	300
Vacuum (max)	mmHgO	3000	3000
Container	l	55	55
Main filter	cmq	14500	14500
Safety filter	cmq	15000	15000
Shaker	-	-	-
Shutter Inlet	mm	70-50	70-50
Noise level	dB(A)	75	75
Dimensions	mm	765x745x1635	765x745x1635
Weight	kg	95	95

Versions:

- Cartridge safety filter Hepa class H13
- Special voltages
- Industrial single phase motor 200/240v
- Stainless steel body
- ATEX version



Durability


	Scraps	Light chips	Dust	Heavy chips	Crush	Sand Mixing sand	Oil Sludge	Liquids	Heavy grease	Welding
DSI 505										

Resistant

Suitable

Excluded

Performance



- Atex, ex in accordance with EN50014 - EN50018
- IP65 Starter
- Shielded electrical cable
- BI ground cord activity
- Cap dust protection

Ex II 3D T125°C IP55

ATEX



COMPANY INFO:
 COMM-CO
 KREEKZOOM 9
 4561 GX HULST
 THE NETHERLANDS

TEL: +311114-370030
 FAX: +311114-370029
 E-MAIL: INFO@COMM-CO.COM
 WEBSITE: HTTP://WWW.COMM-CO.COM
 WEBSHOP: HTTP://WWW.ECOMMSHOP.COM

WWW.ATEXSHOP.COM
 WWW.RUGGEDSHOP.NL
 WWW.WEBPAINTER.NL
 WWW.WAVECOM.COM
 WWW.EYE2CTV.NL