

iCAM501 Intrinsically Safe Zone 0 Digital Camera



Create visual and audio records in the hazardous area....

ATEX II 1 G Ex ia IIB T4 Ga, II 2 G Ex ia IIC T4 Gb

IECEX Ex ia IIB T4 Ga, Ex ia IIC T4 Gb

Group 1 M1 mining certification pending

-20°C to +60°C

IP65

Overview

The iCAM501 intrinsically safe digital camera is the perfect visualisation tool for use in hazardous areas. ATEX and IECEx certified the iCAM501 can be used in all sectors of industry including Chemical & Pharmaceutical plants, Oil & Gas production platforms, Refineries and Mining to name but a few.

Manufactured from rugged injection moulded anti static plastic, the iCAM501 is IP65 rated and is suitable for use in the most arduous environments. Its long slim lightweight enclosure, weighing less than 200g, lends itself to single handed operation, making it convenient to carry in your pocket.

Equipped with its super bright 4 LED flash, anti shake technology and 3.1 mega pixel resolution, the iCAM501 provides high quality images in all Hazardous Area environments.

Data transfer to any computer in the safe area is simple and easy to undertake via a USB port utilising Picture Transfer Protocol (PTP) which is initiated automatically.

All images are date and time stamped to create a chronological history and are coupled to the unique function of Voice Annotation Audio records, which are systematically matched to the image filename.

Features and Benefits

Rugged Housing

The iconic injection moulded Anti static plastic housing is IP65 rated and suitable for use in the most arduous environments

Compact and Lightweight

The long slim camera enclosure lends itself to single handed operation and weighing less than 200g is convenient to carry in your pocket

Super Bright 4 LED Flash

The powerful integrated flash allows for picture capture in very poor light conditions

Voice Annotations

Never forget—record voice notes to store a .wav file with the same filename as the image taken for detailed reports

Anti Shake

High quality images are produced every time, minimising the possibility of blurring.

User Upgradeable

Field upgradeable firmware via USB allows future upgrades to be carried out by the user

3.1 Mega Pixel

High resolution images provide greater detail of equipment or larger areas such as plant rooms and buildings

1GB Memory

Allows for a much higher level of visual/audible data storage Hold approximately 5,000 JPEG images without any audio recording and additional 960Kbytes per minute for audio

Simple Data Transfer

3 Simple Steps— open, connect via a USB port and transfer data utilising the Picture Transfer Protocol (PTP) Certified for direct connection to any PC in the safe area without requiring an external protection barrier

Powered by Primary Cells

Certified for use with leading brand alkaline cells means the camera is always ready to use any time, any place.

Specification

Certification Number	ITS09ATEX26868X, IECEx ITS 09.0027X
ATEX Certification	II 1 G Ex ia IIB T4 Ga, II 2 G Ex ia IIC T4 Gb
IECEx Certification	II 1 G Ex ia IIB T4 Ga, II 2 G Ex ia IIC T4 Gb
FM Certification	Class 1 Div 1 ABCD T4 - Pending
Compliance	EMC: EN 55022 1998 class B, EN 55024 1999 LV: EN 60950 2002 FCC: FCC: Class A device, compliance through verification route
Dimensions	132mm x 32mm x 22mm (5.20" x 1.26" x 0.87")
IP Rating	IP65
Operating Temperature	-20°C to +60°C
Weight	Approx 200g including batteries
Housing	Injection moulded anti static plastic housing
Relative humidity	95% RH non condensing
Power	2 x Alkaline AA batteries, refer to Ex Certificate for details on range of approved batteries
Memory	On board 1Gbyte NAND Flash (holds approx 5,000 JPEG images without any audio recording and additional 960Kbytes per min for audio)
Image	3.1 Mega-Pixel (2048 x 1536 resolution)
Lens	Fixed focus 1/4" format lens in plastic holder
Focal Distance	30 cm to infinity
View Finder	Two element optical view finder
Power Modes	Operate and auto power-down (after 2 mins)
Battery Life	Up to 800 shots without flash and up to 150 shots with flash taken one after the other. 310 shots as per the CIPA DC-002 standard (mixed mode shots with and without flash) Note it is very difficult to be precise about exact numbers as there are many factors that can influence this such as the ambient temperature, how long the camera is powered up, number of voice recordings made and the number and length of time it is connected to a PC for transferring picture and voice data.
Connectivity	USB 1.1 via mini-USB socket for use in the safe area only. Certified for direct connection to a PC without requiring an external protection barrier
OS Support	PTP imaging device in Windows 2000/XP/Vista/7, Mac OsX 10.x and most versions of Linux. USB firmware upgrade utility for Windows XP/2000/Vista/7 only.
Flash	4 LED flash giving 43.7 lux.seconds of energy at 67ms exposure
Audio recording format	wav
Image format	jpeg
Time and Date	Time and date stamping of stored images Time and date set via Picture Transfer Protocol (PTP) automatically

Ordering Information

Description

Intrinsically safe zone 0 digital camera including lanyard and 2 x AA batteries

Part Number

iCAM501