



Intrinsically-Safe Handlamp H-4 DC A



Technical data:

Ambient temperature Ta: -4°F to +104°F (-20°C.....+40°C)

Storage temperature: $-4^{\circ}F$ to $+104^{\circ}F$ ($-20^{\circ}C$ $+40^{\circ}C$)

Operating time: up to 20 hours

Dimensions: $7.4" \times 5.1 \text{ (L} \times \text{ø)} \text{ (190 mm} \times 130 \text{ mm)}$

Weight: approx. 49.4 oz (1400 g) (with battery pack)

Ingress protection: IP 66

Power supply: 4 x Type D batteries LR20/R20

Bulb: halogen 4.8V and 0.5 A type H-141

The safety lamp H-4 DC A is a powerfull flashlight for explosion-hazardous areas (exept firedamp endangered mining) of zone 2 and 1 as well as of zone 22 and 21 according to IEC/CENELEC.

- •Long-life Halogen light bulb
- Robust, shockproof, antistatic casing
- •Standard batteries LR20/R20

Ex-data:

Ex designation:

©II 2 GD EEx e ib IICT4

EC-Certificate of conformity: BAS 01 ATEX 2187

Scope of supply:

Intrinsically-Safe Handlamp H-4 DC A incl. batteries

Accessories:

spare bulb type H-141 4.8V