

Intrinsically-Safe Torches Lite-Ex 15, 20, 23, 25

Lite-Ex ...

...non-sparking aircraft aluminium!

The ultimate range of intrinsicallysafe torches - with handy features such as adjustable beam focus, antiroll device and integrated spare bulb. Housed in a solid metal casing that has integral rubber rings to provide a sure grip in hazardous areas.

Standard accessories:

- Lite-Ex with integrated spare bulb
- Batteries

Accessories:

Lite-Ex 25

- •Leather carry case, spare lens
- •Spare bulb type AC2C/2D/BB

Lite-Ex 23

- •Leather carry case, spare lens
- •Spare bulb type AC2C/2D/BB

Lite-Ex 20

- •Leather carry case, spare lens
- •Spare bulb type AC2300/BB

Lite-Ex 15

- •Leather carry case, spare lens
- •Spare bulb type AC2640/BB



Lite-Ex 25 Lite-Ex 23 Lite-Ex 20 Lite-Ex 15 **Ambient** temperature Ta: -20°C...+40° -20°C...+40° -20°C...+40° -20°C...+40° $2 \times LR 14$ 2 x LR 6 2 x LR 6 Power supply: $2 \times LR 20$ AMPERCELL AMPERCELL **AMPERCELL AMPERCELL** Bulb: AC2C/2D/BB AC2C/2D/BB AC2C/2D/BB AC2C/2D/BB Operating time: up to 17 h up to 9 h up to 5 h up to 4,5 h IP 54 IP 54 IP 54 IP 54 Ingress protection:

approx. 740 g approx. 420 g approx. 152 g approx. 120 g

Technical data:

Weight:

Ex-data:

Ex designation:

© II 2 G EEx e ia IIC T4
EC-Certificate of conformity:
TÜV 99 ATEX 1409