## **EXECUTIVE 1.0**





Optional Accessory	Spare battery with double capacity
	AC charger
	Vehicle charger
	Vehicle mount
	Headset
	USB cable
	Quick start guide
Operating system	Genuine Windows Mobile <sup>®</sup> 6.5
	Professional
Mahila Computing	
	Qualcomm MSM7227, 600 MHz
Platform	
Display	3,2"-TFT-LCD, HVGA (480 x 320)
Display	Pressure sensitive touchscreen
Champer O. Manager	
Storage & Memory	
	512 MB-NAND-Flash
Keypad	4 x functional key x 4
	2 x Volume control key
	1 x Camera key
	1 x Power key
Expansion Slots	1 x micro SD-card slot
	(up to 32GB SDHC memory card) 1x
	1. USD (Client 2.0: 4 min Minne D
IO Interface	1 x USB (Client 2.0; 4-pin, Micro-B-
	type;
	DC-power-in (5 V, 1 A)) x1
	Audio output x 1
	Microphone x 1
	Speaker x 1
Communication-	WWAN (HSUPA / HSDPA / UMTS /
interface	EDGE / GPRS / GSM)
	802.11 b/g
	Bluetooth (v2.1+EDR-class 2)
	GPS with A-GPS support-
	(with internal antenna)
	www.atexshop.com
	www.ruggedshop.nl

## Advantages:

- 1. MIL-STD-810G-Compliance
- 2 3,2" Display HVGA-TFT-LCD
- **3.Touchscreen pressure sensitive**
- 4. Dust- and waterproof (IP65)
- 5. Microsoft Windows Mobile<sup>®</sup> 6.5 Professional
- 6. 3,2-Megapixel Camera
- 7. GPRS, UMTS, EDGE, HSDPA, Bluetooth, Wi-Fi
- 8. Micro SD-cards up to 32 GB
- 9. Long battery life time
- 10. Robust industrial device

Company info: Comm-Co Kreekzoom 9 4561 GX Hulst The Netherlands Tel: +31114-370030 Fax: +31114-370029 E-mail: info@comm-co.com Website: http://www.comm-co.com Webshop: http://www.ecommshop.com

www.atexshop.com www.ruggedshop.nl www.webpainter.nl www.wavecomblog.com www.eyecctv.nl

## **EXECUTIVE 1.0**

The Netherlands

## E ATEXSHOP.COM

THE LARGEST GLOBAL DISTRIBUTOR IN ATEX > 350 PRODUCTS

www.eyecctv.nl

Inbox Accessory	AC charger	ATEX certification	Ex-Zone 2
	USB cable		😡 II 3 G Ex ic IIC T4
	Hand strap stylus Quick start guide		
	Battery	Regulation	CE, FCC, A-Tick, cTUVus
	Headset		
	Screwdriver	<b>Rugged Features</b>	MIL-STD-810G and IP65 certified
Calleran			Tamper-proof plastic case
Software	Microsoft Internet Explorer Mobile®		Drop resistant (26 drops from 1,52 m
	Microsoft <sup>®</sup> Windows Media <sup>®</sup>		/ 5 ft)
	Player 10 Mobile		Tumbling resistant (250 cycles; 0,5 m
			/1.6 ft)
Camera	3,2 Megapixel-Fixfocus-Camera		
		Environmental	Temperature:
Alphanumeric Data	<b>a</b> Soft Input Panel- (SIP-) on screen	Specification	- Operating: -21°C to 43°C
Entry	keyboard	Specification	- Storage: -25°C to 63°C
,	Transcriber handwriting recognition		Humidity:
	Nuance XT9 <sup>™</sup> SIP		- 95% RH, non-condensing,
Security-	Wi-Fi for WPA-/WPA2-operation		
Features	Authentification: OPEN, SHARED-KEY,	Description:	
reatures	PEAPv0/EAPMSCHAPv2,	Description.	
	EAP-TLS		nd IP65 certified and MIL-STD-810G
	Encryption: WEP, AES, TKIP	•	<b>TIVE 1.0</b> is a fully rugged
		•	ant to liquid, dust and shocks. Its
Power	AC-adapter (5W, 100 - 240VAC;		ocket-friendly design allows users to
	50 / 60 Hz)	-	of this device, also a valuable work
	Li-Ion smart battery (1030 mAh)	partner, wherever	they are.
	(up to 4 hours of battery life)	EXECUTIVE 1 0 feat	tures impeccable scalability and
			naximum 32GB microSD memory
Dimension &		•	ctions including 3.75G WWAN, GPS
	13,6 x 7,0 x 2,5 cm, (5.35" x 2.76" x	and Bluetooth, bringing users smooth communication	
Weight	0.98")	and data transmission anytime, anywhere.	
	215 g (7.58 oz)		
			ts in mind, EXECUTIVE 1.0 comes
Article number :	E0100000		dows Mobile <sup>®</sup> 6.5 Professional
			or a seamless integration with
		-	cture as well as easier application
		•	ving clients to achieve optimal
			y. <b>EXECUTIVE 1.0</b> as a fully rugged with its design for prolonged
			presents businesses with the most
			ion as it will enable companies to
	Remarks: technical details can		f ownership (TCO) dedicated to
	change.		ance and replacement.
Company info:	Tel: +31114-370030		www.atexshop.com
Comm-Co	Fax: +31114-370029		www.ruggedshop.nl
Kreekzoom 9	E-mail: info@comm-co.com		www.webpainter.nl
4561 GX Hulst	Website: http://www.comm-co.com www.wavecomblog.com		

Webshop: http://www.ecommshop.com