



### IS-MP.2

The IS-MP.2 is a handheld reader for easy and efficient reading of RFID/NFC TAGs that are located closely together or positioned in areas that are difficult to access. The TAG information can be viewed directly on the OLED display, transferred via Bluetooth or read from the storage via USB.

#### TECHNICAL FEATURES



ATEX approval:  
EX-zone 2/22  
Ⓜ II 3G Ex ic IIC T4 Gc  
IP54  
Ⓜ II 3D Ex ic IIIB T135°C  
Dc IP54



IECEx approval:  
EX-zone 2/22  
Ⓜ Ex ic IIC T4 Gc IP54  
Ⓜ Ex ic IIIB T135°C Dc  
IP54



vibration feedback



size:  
190 x 30 x 35 mm,  
weight: 125 g



battery capacity  
for 2000 Bluetooth  
readings



memory for  
1000 readings



Bluetooth® 4.0 LE



OLED-display



1 ... 3 cm  
reading distance



RFID/NFC tag-reader\*:  
LF 125kHz,  
LF 134,2 kHz  
FDX-B + HDX,  
HF und NFC 13,56 MHz,  
UHF 868 MHz



#### FURTHER FEATURES



IP54 certified



operation range from  
-20 °C to 60 °C



real-time clock



apps with remote use  
available

\* = Allows individual configuration.

#### CONTENTS

IS-MP.2, USB cable, quick start manual and safety instructions