



ITEM NO. KNEX6 Analogue Explosion proof telephone with loudspeaker and light

DESCRIPTION

- 1. Robust aluminium alloy die-cast body, Vandal & tamper-resistant hardware
- 2. Waterproof rating IP66 dust proof.
- 3. Full keypad with memory, 10 button programmable telephone, support free dial.
- 4. Magnetic reed hook-switch.
- 5. Heavy Duty handset with hearing Aid compatible receiver, Noise canceling microphone.
- 6. Handset with industrial strong curly cord .
- 7. Stainless Steel keypad keep waterproof and dusty proof.
- 8. Door cover: orient automatically and good self closing, convenient for use.
- 9. Temperature range from -40 degree to +70 degree.
- 10. The housing covered with a layer of reflective label for easy identification at night.
- 11. Powder coated in UV stabilized polyester finish.

12. Application: Hazardous dust and gas atmospheres, petrochemical industry, Tunnel, metro, railway, LRT, speedway, marine, ship, offshore, mine, power plant, bridge etc.

Specification

Types of protection: Il 2G Ex db ib IIB T4 Gb -40°C to 60°C DTMF dialling MTBF:100000hours With built-in amplifier and with external speaker 15-30W With flash light Power supply:Telephone line Auxiliary Contacts:1 Aux Output, dry contact Contact Ratings. Load: Resistive load



KNSP-18

Rated load:0.3 A at 125 VAC; 1 A at 30 VDC Rated carry current:1A Max.switching voltage:125 VAC,60VDC Max.switching current:1A Sound level of ringing:over 120dB(A). speed dialling keypad:Super strong function is available for dialling 12 groups of numbers stored in the memory Housing: construction robust aluminium alley die-cast body Unit size: 278X349X161MM Weight: 8kg Environment conditions: Ambient temperature: -40°C to 70°C. Relative humidity:10%~95% Atmospheric pressure: 86~106Kpa Circumstance noise:less than 60dB(A) Degree of protection: IP66 according to EN60529 Impact protection: IK 09 according to EN50102

> Comm-Co B.V. Kreekzoom 9, 4561 GX, Hulst The Netherlands Tel: +31 114-370030 Email: info@comm-co.com

The telephone layout

