

Experience the freedom of wireless scanning with the Unitech MS842P (wireless version of the new MS842 series) high-performance barcode scanner.

Like all MS842 series models the MS842P supports all common 1D and 2D barcodes and high-density barcodes with the HD option. With the integrated 2.4G mobility and its ergonomic design the MS842P offers great comfort and freedom to move around without being disturbed during any scanning tasks.

Mobility, durability and reliability

With the ability to scan up to 10m via its USB dongle the MS842P provides flexibility and productivity for users. Unitech's MS842P is a great solution for your short wireless scanning needs such as retail store inventory management or extended flexibility in warehouse checkout counters. The MS842P stores data in a buffer mode while it is out of range of the wireless signal and uploads this data when it gets back in range.

The Plug and Play design makes it very easy to setup and integrated the MS842P for any business surrounding.

Great 2D scanning solution

With the seamless integration of a high-performance decoder and scan engine, the MS842P is a great tool to improve productivity for a wide range of markets and applications. No doubt Unitech's MS84P provides one of the most efficient scanning solutions in its class.

Main features

- Built in high performance 2D engine & decoder
- Optional HD reader
- Durable, Compact and Long life trigger design
- Trigger mode, continuous mode and presentation mode
- 2.4G mobility wireless design 10m operation range
- Buffer mode when out of range
- Easy Plug and Play USB dongle receiver
- Cradle for charging or to host dongle receiver and scanner
- Rugged design by IP42 and 1.8m drops





Operational & Performance

Technology CMOS Imager sensor Light source Illumination: LED (625nm) Aiming: Laser (655nm)

Resolution 752 x 480 Max. 95.000 Lux Ambient Light Immunity Skew: ±60° Reading angle

Pitch: ±60° Beeper (adjustable tone)

Reading distance (DOF)

Reading indicators

3			
Standard	near	far	
Code 39, 5mil	5.3cm	19.1cm	
PDF417, 6.7mil	8.6cm	18.0cm	
UPC / EAN	4.1cm	39.4cm	

High resolution	near	far
Code 39, 3mil	4.1cm	9.7cm
PDF417, 4mil	4.6cm	8.9cm

Symbologies

Decode Capability

1D: Code 39, Full ASCII Code39, Interleave 2 of 5, Standard 2 of 5, UPC A/E, Delta Code, Label Code, MSI/ Plessy, Codabar, Code 11, EAN8/13, Code 93, Code 128, EAN128, Code32, Toshiba Code, GS1 databar Code.

2D: PDF417, MicroPDF417, Datamatrix, QR Code, Micro QR Code, Aztec, RSS, Composite, TLC -39, MaxiCode.

Postal: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX).

Power Source

DC 3V to 5V Operation voltage Operating Time Over 10 hours Battery Type Lithium-ion

Battery Capacity 1620mAh charged via cradle Battery Charging time Fully charged in 4 hours

Data Formatting

Prefix, Suffix, Code ID, Reformatting Date

Operation mode

Trigger mode, Presentation mode, Flash Mode, Continuous Mode, Buffer mode

Connectivity

Unlicensed 2.4GHz Radio Frequency Wireless, SPP & HID profiles Protocol

10m (line of sight) Range USB (via Cradle or dongle)

Host Interface supported

Enclosure

Scanner dimension Scanner weight Cradle dimension Switch life

176mm x 74 mm x 89mm 210g (without cable) 73 x 95 x 200 mm 10 million time

Environmental

Operating temperature Storage temperature Relative humidity Drop test to concrete IP rate ESD protection

-30°C to 70°C 95% non-condensing 1.8 meter (scanner only)

Functional after 8K contact and 12K air

0°C to 50°C

Accessories

Cradle Dongle Battery pack Power adapter USB cable

Warranty

1 year

Regulatory approvals CE, FCC, BSMI, VCCI

Unitech Europe

Tilburg, The Netherlands

• Tel.: +31 (0)13 460 9292

• Email: Info@eu.ute.com

• Website: http://eu.ute.com







Company Info: Tel:31114-370030 Comm-Co Fax: +31114-370029

Kreekzoom 9 E-mail: Info@comm-co.com

4561 GX Hulst Website: http://www.comm-co.com The Netherlands Webshop: http://www.ecommshop.com

www.atexshop.com www.ruggedshop.nl www.webpainter.nl www.wavecomblog.com www.eyecctv.nl