



Operational Handheld (OPH)

Radio Characteristics		Dimensions & Weight			
Frequency bands	GSM-R, ER-GSM, GSM 900, E-GSM 900, DCS 1800	Height	145 mm		
Transmitting power	2 W (GSM / GSM-R), 1 W (DCS 1800)	Width	60 mm		
Data transmission	GPRS class 10	Depth	36 mm		
Modulation type	GMSK	Weight (incl. battery)	ca. 300 g		
Environmental Characteristics					
Operating temperature	-25 °C to 70 °C				
Storage temperature	-40 °C to 85 °C				
Protection class	IP65 (dust- and water-resistant)				
Chemical resistance	against influences from brake fluid, engine and gearbox oil				
Technical Data					
Display	2.2" TFT colour display, 240 x 320 pixels (QVGA)				
Audio	2 microphones, 2 loudspeakers				
Battery	2900 mAh (Lithium-Polymer battery)				
Interfaces	peripheral accessory interface & RS 232 (remote microphone, headset, etc.)				
Extras					
OTA - SIM upgrade support	automatic band recognition	GSM ASCII application (phase 2+)			
GPS optional	GSM-R application without shunting mode				
Functional Characteristics					
usable with gloves	left side PTT button(right side optional)	MicroSD card slot			
Walkie-Talkie mode	microphone muting	audio recorder / player			
quick dialling register	automatic redialling	Tilting sensor optional			
configuration cloning	RF monitor	SMS			
menu scroll & select	LED indication for status and operation mode				
emergency call audio recorder	remote control by external operating device				
automatic hang-up after call	configuration and software update via external interface				



Accessories



	Quad charger right-hand button	Desktop charging station	Desktop charger	Desktop charger	Multi Power Supply	Adapter cable	Car charger	Charging cradle
Push-To-Talk (PTT) right-hand button								
Leather Bag Type 3								
Leather Bag Type 2								
Push-To-Talk (PTT) right-hand button								
Remote speaker microphone Aure- lis-Audio DAT1								
4-Point Shoulder Strap								
3-Point Shoulder Strap								
2-Point Shoulder Strap								
1-Point Shoulder Strap								
Headset								
Helmet set								
FireTalk								
Aurelis								

Comm-Co B.V.

Kreekzoom 9, 4561 GX, Hulst

The Netherlands

Tel: +31 114-370030

Email: info@comm-co.com

COMM-CO
Communication today and tomorrow