

Getac recommends Windows 10 Pro for business

" We sell what you need;

not what we have!"



UX10-EX FULLY RUGGED TABLET

- ATEX & IECEx explosive atmosphere certified
- 10th Generation Intel® Core™ i7 / i5 Processor
- 10.1" FHD LumiBond® 2.0 display with Getac sunlight readable technology (1,000 nits) and capacitive touchscreen
- Multi-functional hard handle for on-the-job flexibility
- Multiple configurable options to fit diverse usage scenarios















Specifications

Operating System

Windows 10 Pro

Mobile Computing Platform

Intel® Core™ i5-10210U Processor 1.6GHz Max. 4.2GHz with Intel® Turbo Boost Technology
- 6MB Intel® Smart Cache

Platform options:Intel® Core™ i5-10310U vPro™ Processor 1.7GHz
Max. 4.4GHz with Intel® Turbo Boost Technology 6MB Intel® Smart Cache

Intel® Core™ i7-10510U Processor 1.8GHz Max. 4.9GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache

Intel® Core™ i7-10610U vPro™ Processor 1.8GHz Max. 4.9GHz with Intel® Turbo Boost Technology 8MB Intel® Smart Cache

VGA Controller

Intel® UHD Graphics

Display

10.1" IPS TFT LCD WUXGA (1920 x 1200) Anti-static protection film
1,000 nits LumiBond® display with Getac sunlight Capacitive multi-touch screen

Storage & Memory

8GB DDR4

Optional: 16GB/32GB DDR4

256GB PCIe NVMe SSD

Optional: 512GB / 1TB PCIe NVMe SSD **Keyboard**

Power button

5 tablet programmable buttons

Pointing Device

Touchscreen

- Capacitive multi-touch screen
 Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Optional (top side): 1D/2D imager barcode reader, or Serial port, or USB 3.2 Gen 1 Type-A port, or USB 3.2 Gen 1 Type-C port, or LAN port (RJ45), or VGA port ', or HF RFID reader "

I/O Interface

FHD webcam x 1 ⁱⁱⁱ 8M pixels auto focus rear camera x 1 Audio in/out combo x 1 DC in Jack x 1 USB 3.2 Gen 2 Type-A x 1

Optional: Windows Hello face-authentication camera (front-facing) x 1 iii

Communication Interface Intel® Wi-Fi 6 AX200, 802.11ax Bluetooth (v5.2) ^{iv} Optional: Dedicated GPS ^v Optional: 4G LTE mobile broadband with integrated GPS ^v

Optional: 10/100/1000 base-T Ethernet **Security Feature**

TPM 2.0 Kensington lock Optional: Intel® vPro™ Technology Optional: HF RFID reader

AC adapter (65W, 100-240VAC, 50/60Hz) Li-ion smart battery (11.1V, typical 4200mAh; min. 4080mAh) x 1 Optional: High capacity battery (10.8V, 9240mAh) x 1

Dimension (W x D x H) & Weight

276.8 x 194.5 x 23.5mm (10.89" x 7.65" x 0.92") 1.24kg (2.73lbs) ^{vi}

Rugged Feature

MIL-STD-810H certified IP65 certified Vibration & 6ft (1.8m) drop resistant vii

ATEX & IECEx certified **Environmental Specification**

Temperature 1

- Operating: -21°C to 63°C / -6°F to 145°F Storage: -51°C to 71°C / -60°F to 160°F
- 95% RH, non-condensing

Explosion Protection

ATEX/IECEx Zone 2/22 Ex II 3G Ex ic op is IIC T4 Go Ex II 3D Ex ic op is IIIB T130°C Dc

Pre-installed Software

Getac Utility Getac Camera Getac Geolocation Getac Barcode Manager ix Optional: Absolute Persistence®

Accessories

Battery (11.1V, typical 4200mAh; min. 4080mAh) AC adapter (65W, 100-240VAC) Capacitive stylus with tether

Battery (11.1V, typical 4200mAh; min. 4080mAh) High capacity battery (10.8V, 9240 mAh) Multi-Bay charger (Dual-Bay) Multi-Bay charger (Eight-Bay) AC adapter (65W, 100-240VAC) Digitizer pen

Capacitive stylus with tether Anti-static protection film

Shoulder strap (2-point) Shoulder harness (4-point; handsfree) 100W Type-C adapter

Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- 1D/2D imager barcode reader, Serial port, USB 3.2 Gen 1 Type-A port, USB 3.2 Gen 1 Type-C port, LAN port (RJ45) and VGA port are mutually exclusive options.
- 13.56MHz contactless HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options.
- Bluetooth performance and connectable distance may be subject to interference with distance may be subject to interference with
 the environments and performance on client
 devices, users may be able to reduce effects of
 interference by minimizing the number of
 active Bluetooth wireless devices that is
 operating in the area.
 v Supports GPS and Glonass.
 vi Weight and dimensions vary from
 configurations and optional accessories.
 vii Drop test results vary from configurations and
 optional accessories.

- optional accessories
- viii Tested by an independent third-party test lab following MIL-STD-810H.

 ix Available when barcode reader option is selected.

UX10-EX **Fully Rugged**

Tablet



COMM-CO

" We sell what you need;

not what we have!"